

X-PROTECTOR





Description:

The sealant it is a product made from latest-generation raw materials and has a long-lasting effect on the treated surface. Its active ingredients penetrate into the surface's micropores and provide sound protection that will help water slide, thereby preventing dirt from building up and making surfaces easier to clean. Provides a self-cleaning action on sloping surfaces.

Directions for use:

- Cleaning: for heavy soiling (intense grease, bird droppings, etc), first provide rough cleaning with normal neutral detergent and rinse. Then degrease with an alcohol-based product and do not touch with bare hands.
- Sealing: apply the product onto the entire clean and dried surface; apply with a wet sponge or cloth. It is also possible to spray the product abundantly from a distance of 5-10 cm. The recommended dosage is 10-25 ml per m² and work on areas measuring about 1 sqm.
- Polishing: wait for 3 minutes and immediately polish with a clean microfiber cloth. The solution evaporates immediately, therefore, if required, a second coating can be applied. Do not wet the treated surface for at least 30 minutes.

CAUTION:

- Do not use with temperatures below 5°C; the ideal temperature is between 15-25 °C.
- Do not expose the surface to direct sunlight when applying the product.
- Thorough preliminary cleaning is an essential requirement for the chemical bonding and duration of the sealant.
- Once opened, the bottle must be used within 4 months.

To handle the product follow the precautionary advice on the safety data sheet.

Technical Features:

Appearance and colour: Slightly amber liquid

Odour: characteristic

pH: n.d.

Flash point: <23°C

Relative density: 0,82 g/cm3 Solubility in water: soluble

Unopened and stored at room temperature away from direct sunlight.

Packaging

ART. CODE

1 L BOTTLE + 30 ml dispenser cap (6 cps) 76861 JERRY CAN 5 Lt 77197

> FRA-BER s.r.l. Head of the Laboratory

Original signed document available at the company's headquarters. The data contained is the result of technological research of our laboratory and is provided for information purposes only. We exclude any liability arising from an incorrect choice of product and the lack of the necessary precautions, which must always be verified by the user.



